
PyReportJasper

Release 2.1.0

Nov 30, 2020

Contents

1	Installation	3
1.1	Binary Install	3
1.2	Source Install	3
2	PyReportJasper User Guide	7
2.1	PyReportJasper Introduction	7
3	API Reference	9
3.1	Class Config	9
3.2	Class Report	13
3.3	Class Db	14
4	Changelog	17
5	Indices and tables	19
	Index	21

This package aims to be a solution to compile and process JasperReports (.jrxml & .jasper files).

Did you ever had to create a good looking Invoice with a lot of fields for your great web app or desktop?

I had to, and the solutions out there were not perfect. Generating *HTML* + *CSS* to make a *PDF*? WTF? That doesn't make any sense! :)

Then I found **JasperReports** the best open source solution for reporting.

From their website:

The JasperReports Library is the world's most popular open source reporting engine. It is entirely written in Java and it is able to use data coming from any kind of data source and produce pixel-perfect documents that can be viewed, printed or exported in a variety of document formats including HTML, PDF, Excel, OpenOffice and Word.

PyReportJasper is available either as a pre-compiled binary for Anaconda and PYPI, or may be built from source through various methods.

1.1 Binary Install

PyReportJasper can be installed as pre-compiled binary if you are using the [Anaconda](#) Python stack. Binaries are available for Linux, OSX, and windows on conda-forge.

1. Ensure you have installed Anaconda/Miniconda. Instructions can be found [here](#).
2. Install from the conda-forge software channel:

```
conda install -c conda-forge pyreportjasper
```

1.2 Source Install

Installing from source requires:

Python PyReportJasper works CPython 3.5 or later. Both the runtime and the development package are required.

Java Either the Sun/Oracle JDK/JRE Variant or OpenJDK. PyReportJasper has been tested with Java versions from Java 1.9 to Java 15.

Jpype1 JPype is a Python module to provide full access to Java from within Python.

Once these requirements have been met, one can use pip to build from either the source distribution or directly from the repository. Specific requirements from different architectures are listed below.

1.2.1 Build using pip

PyReportJasper may be built and installed with one step using pip.

To install the latest PyReportJasper, use:

```
pip install pyreportjasper
```

This will install PyReportJasper either from source or binary distribution, depending on your operating system and pip version.

To install from the current github master use:

```
pip install git@github.com:PyReportJasper/pyreportjasper.git
```

More details on installing from git can be found at [Pip install](#). The git version does not include a prebuilt jar the JDK is required.

1.2.2 Build and install manually

PyReportJasper can be built entirely from source.

1. Get the PyReportJasper source

The PyReportJasper source may be acquired from either [github](#) or from [PyPi](#).

2. Build the source with desired options

Compile PyReportJasper using the included `setup.py` script:

```
python setup.py build
```

3. Test PyReportJasper with (optional):

```
python -m unittest discover ./test -p '*.py'
```

4. Install PyReportJasper with:

```
python setup.py install
```

1.2.3 If it fails...

Most failures happen when `setup.py` is unable to find the JDK home directory which should be set in the environment variable `JAVA_HOME`. If this happens, perform the following steps:

1. Identify the location of your JDK systems installation and set the environment variable.

```
export JAVA_HOME=/usr/lib/jvm/java-11-openjdk-amd64/
```

2. If that `setup.py` still fails please create an Issue [on github](#) and post the relevant logs.

1.2.4 Platform Specific requirements

PyReportJasper is known to work on Linux, OSX, and Windows. To make it easier to those who have not built CPython modules before here are some helpful tips for different machines.

Debian/Ubuntu

Debian/Ubuntu users will have to install `g++` and `python-dev`. Use:

```
sudo apt-get install g++ python-dev python3-dev
```

Windows

CPython modules must be built with the same C++ compiler used to build Python. The tools listed below work for Python 3.5 to 3.9. Check with [Python dev guide](#) for the latest instructions.

1. Install your desired version of Python (3.5 or higher), e.g., [Miniconda](#) is a good choice for users not yet familiar with the language
2. For Python 3 series, Install either 2017 or 2019 Visual Studio. [Microsoft Visual Studio 2019 Community Edition](#) is known to work.

From the Python developer page:

When installing Visual Studio 2019, select the Python development workload and the optional Python native development tools component to obtain all of the necessary build tools. If you do not already have git installed, you can find git for Windows on the Individual components tab of the installer.

When building for windows you must use the Visual Studio developer command prompt.

2.1 PyReportJasper Introduction

This package aims to be a solution to compile and process JasperReports (.jrxml & .jasper files).

3.1 Class Config

class Config (*args, **kwargs)

Class for defining the settings to generate the reports.

jvm_maxmem

Maximum memory used by the JVM

Type str

Value '512M'

jvm_classpath

The class path is the path that the Java runtime environment searches for classes and other resource files.

Type str

dbType

Data source type

Type str

Options None, csv, xml, json, jsonql, mysql, postgres, oracle, generic

dbDriver

Jdbc driver class name for use with dbType: generic

Type str

dbHost

Database host

Type str

dbName
Database name

Type str

dbPasswd
Database password

Type str

dbPort
Database port

Type int

dbSid
Oracle sid

Type str

dbUrl
Jdbc url without user, passwd with dbType: generic

Type str

dbUser
Database user

Type str

jdbcDir
Directory where jdbc driver jars are located.

Type str

input
Input file (.jrxml,jasperl,jrprint)

Type str

dataFile
Input file for file based datasource

Type str

csvFirstRow
First row contains column headers

Type bool

csvColumns
Comma separated list of column names

Type list(str)

csvRecordDel

CSV Record Delimiter - defaults to line.separator

Type str

csvFieldDel

CSV Field Delimiter - defaults to “,”

Type str

csvCharset

CSV charset - defaults to “utf-8”

Type str

xmlXPath

XPath for XML Datasource

Type str

jsonQuery

JSON query string for JSON Datasource

Type str

jsonQLQuery

JSONQL query string for JSONQL Datasource

Type str

locale

Set locale with two-letter ISO-639 code or a combination of ISO-639 and ISO-3166 like en_US.

For a complete list of locales see [Supported Locales](#)

Type str

output

Directory or basename of outputfile(s)

Type str

outputFormats

A list of output formats

Type list(str)

Options pdf, rtf, docx, odt, xml, xls, xlsx, csv, csv_meta, ods, pptx, jrprint

params

Dictionary with the names of the parameters and their respective values.

Example: { 'NAME_PARAM_1': 'value param 1', 'NAME_PARAM_2': 'value param 2' }

Type dict

printerName

Name of printer

Type str

reportName

Set internal report/document name when printing

Type str

resource

Path to report resource dir or jar file. If <resource> is not given the input directory is used.

Type str

writeJasper

Write .jasper file to input dir if jrxml is processed

Type bool

Value False

outFieldDel

Export CSV (Metadata) Field Delimiter - defaults to “,”

Type str

outCharset

Export CSV (Metadata) Charset - defaults to “utf-8”

Type str

askFilter

Type str

Options a - all (user and system defined) params

ae - all empty params

u - user params

ue - empty user params

p - user params marked for prompting

pe - empty user params marked for prompting

classmethod has_output ()

Valid if there is a path or file for the output

Returns Returns true if there is a defined path or file for output otherwise false.

Return type bool

classmethod is_write_jasper ()

Valid if it is to generate a .jasper

Returns Returns `true` if the .jasper is to be generated, otherwise it is `false`.

Return type `bool`

classmethod `has_jdbc_dir()`

Validates if there is a path or file for jdbc .jar

Returns Returns `true` if it exists, otherwise `false`.

Return type `bool`

classmethod `has_resource()`

Validates if there is a .jar or path with several .jar to add to the class path

Returns Returns `true` if it exists, otherwise `false`.

Return type `bool`

3.2 Class Report

class `Report` (*config: Config, input_file*)

Class responsible for instantiating the JVM and loading the necessary Java objects for manipulating the files to compile, generate and export the reports.

Parameters

- **config** (*Config*) – Config class instance
- **input_file** (*str*) – Input file (.jrxml|.jasper|.jrprint)

classmethod `compile()`

Compile the report

classmethod `compile_to_file()`

Emit a .jasper compiled version of the report definition .jrxml file.

classmethod `fill()`

Executes the `fill_internal()` method

classmethod `fill_internal()`

Method responsible for filling the report

classmethod `get_output_stream(suffix)`

Return a file-based output stream with the given suffix

Parameters **suffix** (*str*) – File suffix

Returns Returns an output stream from the input file.

Return type `OutputStream` (java)

classmethod `export_pdf()`

Export the report in pdf format

classmethod `export_rtf()`

Export the report in rtf format

classmethod `export_docx()`

Export the report in docx format

classmethod **export_odt()**
Export the report in odt format

classmethod **export_xml()**
Export the report in xml format

classmethod **export_xls()**
Export the report in xls format

classmethod **export_xls_meta()**
Export the report in xls Metadata Exporter format

classmethod **export_xlsx()**
Export the report in xlsx format

classmethod **export_csv()**
Export the report in csv format

classmethod **export_csv_meta()**
Export the report in csv Metadata Exporter format

classmethod **export_ods()**
Export the report in ods format

classmethod **export_pptx()**
Export the report in pptx format

classmethod **export_jrprint()**
Export the report in jrprint format

classmethod **get_report_parameters()**
Returns a list of all report parameters

Returns Returns a list of parameters

Return type list(str)

classmethod **get_main_dataset_query()**
For JSON, JSONQL and any other data types that need a query to be provided, an obvious default is to use the one written into the report, since that is likely what the report designer debugged/intended to be used. This provides access to the value so it can be used as needed.

Returns Return a string of main dataset query.

Return type str

classmethod **add_jar_class_path(dir_or_jar)**
Method responsible for adding a .jar to class_path or a list of .jar files in an informed directory

Parameters **dir_or_jar** (str) – A .jar file or directory containing one or more .jar

3.3 Class Db

class **Db**
Class responsible for managing the report data source

classmethod **get_csv_datasource(config: Config)**
Method responsible for creating a data source from an informed csv file

Parameters **config** (Config) – Config class instance

Returns Returns a data source of type csv

Return type `net.sf.jasperreports.engine.data.JRCsvDataSource` (java)

classmethod `get_xml_datasource` (*config: Config*)

Method responsible for creating a data source from an informed xml file

Parameters `config` (*Config*) – Config class instance

Returns Returns a data source of type xml

Return type `net.sf.jasperreports.engine.data.JRXmlDataSource` (java)

classmethod `get_json_datasource` (*config: Config*)

Method responsible for creating a data source from an informed json file

Parameters `config` (*Config*) – Config class instance

Returns Returns a data source of type json

Return type `net.sf.jasperreports.engine.data.JsonDataSource` (java)

classmethod `get_jsonql_datasource` (*config: Config*)

Method responsible for creating a data source from an informed json file

Parameters `config` (*Config*) – Config class instance

Returns Returns a data source of type jsonql

Return type `net.sf.jasperreports.engine.data.JsonQLDataSource` (java)

classmethod `get_data_file_input_stream` (*config: Config*)

Get InputStream corresponding to the configured dataFile.

Parameters `config` (*Config*) – Config class instance

Returns Returns a InputStream

Return type `java.io.InputStream` (java)

classmethod `get_connection` (*config: Config*)

Method responsible for obtaining a connection to a database

Returns Returns database connection

Return type `java.sql.Connection` (java)

CHAPTER 4

Changelog

CHAPTER 5

Indices and tables

- `genindex`
- `modindex`
- `search`

A

add_jar_class_path() (*Report class method*), 14
askFilter (*Config attribute*), 12

C

compile() (*Report class method*), 13
compile_to_file() (*Report class method*), 13
Config (*built-in class*), 9
csvCharset (*Config attribute*), 11
csvColumns (*Config attribute*), 10
csvFieldDel (*Config attribute*), 11
csvFirstRow (*Config attribute*), 10
csvRecordDel (*Config attribute*), 11

D

dataFile (*Config attribute*), 10
Db (*built-in class*), 14
dbDriver (*Config attribute*), 9
dbHost (*Config attribute*), 9
dbName (*Config attribute*), 10
dbPasswd (*Config attribute*), 10
dbPort (*Config attribute*), 10
dbSid (*Config attribute*), 10
dbType (*Config attribute*), 9
dbUrl (*Config attribute*), 10
dbUser (*Config attribute*), 10

E

export_csv() (*Report class method*), 14
export_csv_meta() (*Report class method*), 14
export_docx() (*Report class method*), 13
export_jrprint() (*Report class method*), 14
export_ods() (*Report class method*), 14
export_odt() (*Report class method*), 13
export_pdf() (*Report class method*), 13
export_pptx() (*Report class method*), 14
export_rtf() (*Report class method*), 13
export_xls() (*Report class method*), 14
export_xls_meta() (*Report class method*), 14

export_xlsx() (*Report class method*), 14
export_xml() (*Report class method*), 14

F

fill() (*Report class method*), 13
fill_internal() (*Report class method*), 13

G

get_connection() (*Db class method*), 15
get_csv_datasource() (*Db class method*), 14
get_data_file_input_stream() (*Db class method*), 15
get_json_datasource() (*Db class method*), 15
get_jsonql_datasource() (*Db class method*), 15
get_main_dataset_query() (*Report class method*), 14
get_output_stream() (*Report class method*), 13
get_report_parameters() (*Report class method*), 14
get_xml_datasource() (*Db class method*), 15

H

has_jdbc_dir() (*Config class method*), 13
has_output() (*Config class method*), 12
has_resource() (*Config class method*), 13

I

input (*Config attribute*), 10
is_write_jasper() (*Config class method*), 12

J

jdbcDir (*Config attribute*), 10
jsonQLQuery (*Config attribute*), 11
jsonQuery (*Config attribute*), 11
jvm_classpath (*Config attribute*), 9
jvm_maxmem (*Config attribute*), 9

L

locale (*Config attribute*), 11

O

`outCharset` (*Config attribute*), [12](#)
`outFieldDel` (*Config attribute*), [12](#)
`output` (*Config attribute*), [11](#)
`outputFormats` (*Config attribute*), [11](#)

P

`params` (*Config attribute*), [11](#)
`printerName` (*Config attribute*), [12](#)

R

`Report` (*built-in class*), [13](#)
`reportName` (*Config attribute*), [12](#)
`resource` (*Config attribute*), [12](#)

W

`writeJasper` (*Config attribute*), [12](#)

X

`xmlXPath` (*Config attribute*), [11](#)